

PRESTO 190 PRO



The specialist for heavy duty welding for all types of MMA electrodes including cellulosic



16A plug



SAVE ENERGY

Product description and features:

- › More performance 160 @ 50% at 40 °C.
- › With 16 A shuko plug.
- › Suitable for welding with cellulosic electrodes.
- › (VRD) for increased safety when welding on site, e.g. mining sites, shipyards and petrochemical plants.





1126-022



0008-49_r

PRESTO 190 PRO

The PRESTO 190 PRO offers top welding performance with the possibility to adjust both the Arc Force and Hot Start parameters.

Maximum safety is ensured with the **V**oltage **R**eduction **D**evice (VRD) making this equipment suitable for demanding site environments, such as mining, shipyards and petrochemical plants.

This unit is designed for heavy duty use, for welding all types of MMA electrodes, including cellulosic.

Microprocessor controlled, the PRESTO 190 PRO offers excellent arc stability, even with fluctuating input voltage.

The built-in **P**ower **F**actor **C**orrection (PFC) module enables welding with 160 Amps at 50% duty cycle at 40 °C ambient temperature with a primary consumption of only 16A, so PRESTO 190 PRO can be used with a domestic plug.

PRESTO 190 PRO is very versatile and when TIG welding, the slope up and slope down times can be set by the control panel.



2010-080



2010-082

Technical characteristics	PRESTO 190 PRO	
PRIMARY		
Single-phase input voltage	230 V +/- 20% 1Ph / 50-60 Hz	
Effective input current	16 A	
Open circuit voltage	67 V	
Open circuit voltage reduced	14 V	
Welding current range	5 - 160 A	
Duty cycle at 40 °C	at 50%	160 A
	at 60%	150 A
	at 100%	130 A
Connector size	13 mm	
Protection index	IP 23	
Weight	9 kg	
Dimensions	205 x 345 x 450 mm	
European standards	EN 60974.1 - EN 60974.10 Class B	

To order

PRESTO 190 PRO:
W 000 272 661

Options and accessories

Torch holder + earth clamp
KIT ARC 25C50:
W 000 260 684

Tig torch with valve
WTT 26V - 4m:
W 000 266 573

Remote control 10m:
W 000 242 069

Liquid crystal mask
Chameleon 3 F:
W 000 261 351

Delivered equipped with:

- primary cable
- user manual
- safety instructions